


- Timber
- Aluminium
- Concrete



Viroc Acrylic Wall Sealer

Sealing Guide

Modinex Viroc Acrylic Wall Sealer provides a transparent, proactive barrier against oil and water. It protects your composite wall without compromising the surface integrity and assists with removal of oil and water based stains.

1. Surface Preparation

For best results, thoroughly clean the surface from previous coating, stains, dirt and foreign matter before applying. The surface should be clean, dry free of any waxes, coatings or finishes or contaminants.

The prime coat will need to be diluted between 2:1 and 1:1 parts sealer to water depending on the substrate porosity and whether the surface is vertical or horizontal. Apply all coats evenly ensuring that there is no pooling. An undiluted second coat can be applied once the first coat has dried. Dry time could be from 4 hours to 2 days. A third coat may be required. Application can be done with an airless spray gun, roller or brush.

2. Application Method

Test a small inconspicuous area first to determine suitability of purpose. Apply the Wall Sealer liberally in even coats using a new microfiber mop, or lambs wool applicator.

Take care to avoid excessive foam generation and if this occurs lay off the surface quickly with a soft broom to break the foam. Allow 30-60 minutes drying time between coats. The surface is sealed when the sealer no longer soaks into the surface. Wipe off any Wall Sealer solution that has not been absorbed within 10 minutes.

3. For Porous Surfaces

The first coat will completely absorb into the surface. Allow the surface to dry 30-60 minutes and apply a second coat. If the second coat is not absorbed within 10 minutes, wipe off the excess. Some very porous surfaces may require a third coat.

4. Glue and nail up the boards

Wash down the treated surface every few months to keep it clean. When surface needs a refurbishment, powerwash thoroughly and recoat as indicated.

5. Storage

Dispose of contents/container in accordance with local regulations.



Warning Hazard Statements

Harmful if inhaled.

May cause an allergic skin reaction.

Safety (Prevention Statements)

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

First Aid (Response)

Wash contaminated clothing before reuse.

IF ON SKIN: Wash with plenty of soap and water.

CALL A POISON CENTER or doctor/physician if you feel unwell.

IF SKIN IRRITATION OR RASH OCCURS: Get medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

MSDS/data sheet available at: modinex.com.au

Distributed by Modinex Architectural Pty Ltd. Ph: 1800 156 455 Made in Australia

24hr Emergency number: 0438 923 248

Modinex Viroc Acrylic Wall Sealer provides a transparent, proactive barrier against oil and water. It protects your composite wall without compromising the surface integrity and assists with removal of oil and water based stains.

1. Surface Preparation

For best results, thoroughly clean the surface from previous coating, stains, dirt and foreign matter before applying. The surface should be clean, dry free of any waxes, coatings or finishes or contaminants.

The prime coat will need to be diluted between 2:1 and 1:1 parts sealer to water depending on the substrate porosity and whether the surface is vertical or horizontal. Apply all coats evenly ensuring that there is no pooling. An undiluted second coat can be applied once the first coat has dried. Dry time could be from 4 hours to 2 days. A third coat may be required. Application can be done with an airless spray gun, roller or brush.

2. Application Method

Test a small inconspicuous area first to determine suitability of purpose. Apply the Wall Sealer liberally in even coats using a new microfiber mop, or lambs wool applicator.

Take care to avoid excessive foam generation and if this occurs lay of the surface quickly with a soft broom to break the foam. Allow 30-60 minutes drying time between coats. The surface is sealed when the sealer no longer soaks into the surface. Wipe off any Wall Sealer solution that has not been absorbed within 10 minutes.

3. For Porous Surfaces

The first coat will completely absorb into the surface. Allow the surface to dry 30-60 minutes and apply a second coat. If the second coat is not absorbed within 10 minutes, wipe off the excess. Some very porous surfaces may require a third coat.

4. Glue and nail up the boards

Wash down the treated surface every few months to keep it clean. When surface needs a refurbishment, powerwash thoroughly and recoat as indicated.

5. Storage

Dispose of contents/container in accordance with local regulations.



Warning Hazard Statements

Harmful if inhaled.

May cause an allergic skin reaction.

Safety (Prevention Statements)

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

MSDS/data sheet available at: modinex.com.au

Distributed by Modinex Architectural Pty Ltd. Ph: 1800 156 455 Made in Australia

24hr Emergency number: 0438 923 248

First Aid (Response)

Wash contaminated clothing before reuse.

IF ON SKIN: Wash with plenty of soap and water.

CALL A POISON CENTER or doctor/physician if you feel unwell.

IF SKIN IRRITATION OR RASH OCCURS: Get medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

